954 53 48 84
info@landsur.es

ACCESORIOS - BST13500 - HUSAR CABRESTANTE 13500LBS

HUSAR CABRESTANTE 13500LBS

BST 13500lbs Características técnicas
Capacidad de arrastre (cable simple): 13500lbs / 6124 kg
Motor: 6,7 HP / 4,9 kW
Control remoto con cable /inalámbrico
Tren de engranajes planetario de 3 etapas
Relación de transmisión 265:1
Freno de fricción automático
Cable: 22 m x 9,5 mm
Peso neto 34,9 kg
Dimensiones: 535 mm x 160 mm x 251 mm
Guía de 4 rodillos

HUSAR WINCH

WINCH BST 13500 LBS

IP67

Technical specifications

Pull capacity (single line)	13500 lbs/6124 kg
Motor	6,7 HP/4,9 kW
Controls	wired/wireless remote control
Gear	3 - stage planetary
Gear ratio	265:1
Brake	automatic friction brake
Rope	22 m x ø 9,5 mm
Net weight	34,9 kg
Dimensions L x W x H	535mm x 160 mm x 251 mm
Fairlead	4-ways rolles
Mounting bolt pattern	254 mm x 114,3 mm 4-M12

Included :

- hook
- steel rope
- roller fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set

Line speed and motor (first layer)

Line pull	lbs	0	4000	6000	10000	13500
	kg	0	1814	2722	1150	6124
Line speed	m/min 12 V	6,8	3,8	3	2,1	1,2
Motor current	amper 12 V	80	170	210	310	420

Line pull and cable capacity

Layer of cable		1	2	3
Rated line pull per layer	lbs	13500	11500	9600
	kg	6124	5216	4355
Cable capacity per layer	m	6	13	22