



954 53 48 84
info@landsur.es

ACCESORIOS - BSTS3500SYN - HUSAR CABRESTANTE 3500LBS CABLE SINTETICO

CABRESTANTE 3500LBS CABLE SINTETICO

Capacidad de arrastre (cable simple): 3500lbs / 1587 kg

Motor: 1,5 HP / 1,1 kW

Control remoto con cable / inalámbrico

Relación de transmisión: 198:1

Freno de fricción automático

Cable: 12m x 5,5 mm

Peso neto: 10 kg

Dimensiones: 322 mm x 114mm x115,5 mm

Guía deslizante de aluminio







WINCH BST S 3500 LB5

IP67

Technical specifications

Pull capacity (single line)	3500 lbs/1587 kg
Motor	1,5 HP/1,1 kW
Controls	wired/wireless remote control
Gear	3 - stage planetary
Gear ratio	198:1
Brake	automatic friction brake
Rope	12 m x ø 5,5 mm
Net weight	10 kg
Dimensions L x W x H	322 mm x 114 mm x 115,5 mm
Fairlead	aluminium hawse
Mounting bolt pattern	124 mm x 76 mm

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting plate
- mounting screws
- wired remote control
- wireless remote control
- control set

Line speed and motor (first layer)

Line pull	lbs	0	1000	2000	3000	3500
	kg	0	454	907	1360	1587
Line speed	m/min 12 V	4,9	3,2	2,8	2,2	1,8
Motor current	amper 12 V	15	70	105	135	150

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	lbs	3500	2870	2430	2100
per layer	kg	1587	1300	1100	950
Cable capacity	m	2,1	4,6	7,6	12
per layer					