



954 53 48 84
info@landsur.es

ACCESORIOS - BSTS4500SYN - HUSAR CABRESTANTE 4500LBS CON CABLE SINTETICO

CABRESTANTE 4500LBS CON CABLE SINTETICO

Capacidad de arrastre (cable simple): 4500lbs / 2041 kg

Motor: 1,7 HP / 1,3 kW

Control remoto con cable / inalámbrico

Relación de transmisión: 198:1

Freno de fricción automático

Cable: 12m x 5,5 mm

Peso neto: 10,6 kg

Dimensiones: 322mm x 114mm x 115,5 mm

Guía deslizante de aluminio







WINCH BST S 4500 LBS

IP67

Technical specifications

Pull capacity (single line)	4500 lbs/2041 kg
Motor	1,8 HP/1,3 kW
Controls	wired/wireless remote control
Gear	3 - stage planetary
Gear ratio	198:1
Brake	automatic friction brake
Rope	12 m x ø 5,5 mm
Net weight	10,6 kg
Dimensions L x W x H	322 mm x 114 mm x 115,5 mm
Fairlead	aluminium hawse
Mounting bolt pattern	124 mm x 76 mm

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting plate
- mounting screws
- wired remote control
- wireless remote control
- control set

Line speed and motor (first layer)

Line pull	lbs	0	1000	2000	3000	4500
	kg	0	454	907	1360	2041
Line speed	m/min 12 V	4,9	3,2	2,8	2,2	1,4
Motor current	amper 12 V	17	70	105	135	180

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	lbs	4500	3841	3310	2907
per layer	kg	2041	1742	1501	1319
Cable capacity	m	2	4,3	7,2	12
per layer					